

<b>Tadnss-z</b>																			
Maksimalna brzina $v_{max}$	km/h	120																	
Duljina preko odbojnika	mm	21.640																	
Ukupna visina	mm	4.276																	
Razmak središnjih svornjaka	mm	16.600																	
Maksimalna širina	mm	3.065																	
Broj osovina	-	4																	
Prosječna vlastita masa	t	27																	
Nosivost	t	63																	
Ukupna masa vagona	t	90																	
Najmanji polumjer zavoja	m	75																	
Volumen teretnog prostora	m <sup>3</sup>	80																	
Otvor za utovar	Dimenzije	mm <sup>2</sup>	16.800 x 1.200																
	Visina od GRT	mm	4.051																
Otvori za istovar	Dimenzije	mm <sup>2</sup>	450 x 1.480																
	Međusobni razmak	mm	4.066																
	Visina stabilnog dijela od GRT	mm	720																
	Visina pokretnog dijela od GRT	mm	350																
	Udalj.stab.dijela od uzduž.osi vagona	mm	640																
	Udalj.pokret.dijela od uzduž.osi vagona (rad.položaj)	mm	1.000																
Raster graničnih opterećenja	-	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th></th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>S</td> <td>37,0</td> <td>45,0</td> <td>53,0</td> <td>63,0</td> </tr> <tr> <td>SS</td> <td>37,0</td> <td colspan="2">45,0</td> <td></td> </tr> </tbody> </table>				A	B	C	D	S	37,0	45,0	53,0	63,0	SS	37,0	45,0		
			A	B	C	D													
		S	37,0	45,0	53,0	63,0													
SS	37,0	45,0																	
Prijelazna platforma	-	Ima																	
Ručna kočnica	-	Da																	
Okretno postolje	-	Y25Ls(s)d1																	