

# Zatvoreni vagon posebne izvedbe / Closed wagon

Habbins-z (277)



## Tehnički podaci / Technical details

H	zatvoreni vagon posebne izvedbe	Duljina preko odbojnika	23264 mm
	closed wagon	Length over buffers	
a	s 4 osovine	Visina vagona	4270 mm
	with 4 axles	Wagon height	
bb	iskoristiva duljina vagona $l_{u \geq 22}$ m	Visina poda od GTR-a	1202 mm
	usable length of the wagon $l_{u \geq 22}$ m	Floor height from top of the rail	
i	sa otvorenim bočnim stranicama	Osovinsko opterećenje	22,5 t
	with open side doors	Axle load	
n	max. opterećenje $t_{u > 60}$ t	Prosječna vlastita masa	28 t
	max. payload $t_{u > 60}$ t	Average tare weight	
s	max. brzina 100 km/h (s teretom)	Volumen utovarnog prostora	161,4 m <sup>3</sup>
	max. speed 100 km/h (loaded)	Loading capacity	
z	ručna kočnica	Površina utovarnog prostora	62,48 m <sup>2</sup>
	platform-operated hand brake	Loadnig area	
		Širina utovarnog otvora	2840 mm
		Width of loading hatch	
		Duljina utovarnog otvora	22000 mm
		Length of loading hatch	
		Visina utovarnog otvora	2800 mm
		Height of loading hatch	
		Otvor za utovar	10808 x 2800 mm
		Loading opening	
		Broj EUR paleta	63
		No. EUR pallets ☒	
		Broj IP paleta	42
		No. IP pallets ☒	
		Tip zračne kočnice	KE-GP-A
		Air brake type	
Namjena	Prijevoz paleta, papira, celuloze, bijele tehnike, auto dijelova		
Function	Transport of pallets, paper, cellulose, household appliances, car parts		



Raster graničnih opterećenja / Loading chart (t)\*

	A	B	C	D
S	36,0	44,0	52,0	62,0
120	00,0			

\*Granična opterećenja koja su napisana na pojedinom vagonu mogu biti neznatno veća ili manje, ovisno o vlastitoj masi toga vagona / Data in loading chart depend on tare weight

Tip kočnog umetka	2x250 mm	Sivi lijev / Cast iron
Brake block category		LL / Composite

HŽ Cargo d.o.o.

Heinzelova 51, 10 000 Zagreb

[info@hzcargo.hr](mailto:info@hzcargo.hr)