

# Vagoni s pomičnim krovom / Wagons with open roof

Tadds-z (081) - unutrašnjost vagona plastificirana / inside of the wagon plasticized



## Tehnički podaci / Technical details

|             |  |   |                   |
|-------------|--|---|-------------------|
| T           | vagon s pomičnim krovom  | Duljina preko odbojnika                             | 19040 mm          |
|             | wagon with open roof   | Length over buffers                                 |                   |
| a           | s 4 osovine  | Visina vagona                                       | 4250 mm           |
|             | with 4 axles   | Wagon height  |                   |
| dd          | gravitacijski istovar, visoko  | Osovinsko opterećenje                               | 20,0 t            |
|             | gravity emptying, high   | Axle load   |                   |
| s           | max. brzina 100 km/h (s teretom)   | Prosječna vlastita masa                             | 26 t              |
|             | max. speed 100 km/h (loaded)   | Average tare weight                                 |                   |
| z           | ručna kočnica  | Obujam utovarnog prostora                           | 66 m <sup>3</sup> |
|             | platform-operated hand brake   | Loading capacity                                    |                   |
| Namjena     | Prijevoz rasutih tereta koji nemaju oštih bridova                        | Širina utovarnog otvora                             | 1200 mm           |
|             |  | Width of loading hatch                              |                   |
| Function    | Transport of bulk cargo that does not have sharp edges                   | Duljina utovarnog otvora                            | 2 x 7300 mm       |
|             |  | Length of loading hatch                             |                   |
| Granulacija | 1 - 50 mm  | Visina utovarnog otvora                             | 4050 mm           |
|             |  | Height of loading hatch                             |                   |
| Granulation |  | Broj istovarnih otvora                              | 8                 |
|             |  | No. of unloading hatches                            |                   |
| Istovar     | Otvaranje jednog ili više otvora na jednoj strani ili na objema stranama | Razmak istovarnih otvora                            | 3166 mm           |
|             |  | Unloading hatches distance                          |                   |
| Unloading   | Opening of one hopper or all of them on one side or both sides           | Širina presipnog ruba                               | 800 mm            |
|             |  | Width of the overflow edge                          |                   |
|             |  | Visina istovarnog lijevka od gornjeg ruba tračnice  | 500 mm            |
|             |  | Height of the unloading hopper from top of the rail |                   |
|             |  | Tip zračne kočnice                                  | O-GP              |
|             |  | Air brake type                                      |                   |



Raster graničnih opterećenja / Loading chart (t)\*

|     | A    | B    | C    |
|-----|------|------|------|
| S   | 38,0 | 46,0 | 54,0 |
| 120 | 00,0 |      |      |

\*Granična opterećenja koja su napisana na pojedinom vagonu mogu biti neznatno veća ili manje, ovisno o vlastitoj masi toga vagona / Data in loading chart depend on tare weight

|                      |          |                        |
|----------------------|----------|------------------------|
| Tip kočnog umetka    | 1x320 mm | Sivi lijev / Cast iron |
| Brake block category |          | LL / Composite         |

HŽ Cargo d.o.o.

Heinzelova 51, 10 000 Zagreb

[info@hzcargo.hr](mailto:info@hzcargo.hr)