

Vagoni s pomičnim krovom / Wagons with open roof

Tads-z (082)

Tehnički podaci / Technical details

T	vagon s pomičnim krovom	Duljina preko odbojnika	19040 mm
	wagon with open roof	Length over buffers	
a	s 4 osovine	Visina vagona	4250 mm
	with 4 axles	Wagon height	
d	gravitacijski istovar, nisko	Osovinsko opterećenje	20,0 t
	gravity emptying, low	Axle load	
s	max. brzina 100 km/h (s teretom)	Prosječna vlastita masa	26 t
	max. speed 100 km/h (loaded)	Average tare weight	
z	ručna kočnica	Obujam utovarnog prostora	66 m ³
	platform-operated hand brake	Loading capacity	
Namjena	Prijevoz rasutih tereta koji nemaju oštih bridova	Širina utovarnog otvora	1200 mm
		Width of loading hatch	
Function	Transport of bulk cargo that does not have sharp edges	Duljina utovarnog otvora	2 x 7300 mm
		Length of loading hatch	
Granulacija	1 - 50 mm	Visina utovarnog otvora	4050 mm
		Height of loading hatch	
Granulation		Broj istovarnih otvora	8
		No. of unloading hatches	
Istovar	Otvaranje jednog ili više otvora na jednoj strani ili na objema stranama	Razmak istovarnih otvora	3166 mm
		Unloading hatches distance	
Unloading	Opening of one hopper or all of them on one side or both sides	Širina presipnog ruba	800 mm
		Width of the overflow edge	
		Visina istovarnog lijevka od gornjeg ruba tračnice	500 mm
		Height of the unloading hopper from top of the rail	
		Tip zračne kočnice	O-GP
		Air brake type	



Raster graničnih opterećenja / Loading chart (t)*

	A	B	C
S	38,0	46,0	54,0
120	00,0		

*Granična opterećenja koja su napisana na pojedinom vagonu mogu biti neznatno veća ili manje, ovisno o vlastitoj masi toga vagona / Data in loading chart depend on tare weight

Tip kočnog umetka	1x320 mm	Sivi lijev / Cast iron
Brake block category		LL / Composite

HŽ Cargo d.o.o.

Heinzelova 51, 10 000 Zagreb

info@hzcargo.hr